

## X-ray irradiation system

*This small cabinet is designed mainly to be used in laboratories. Its main purpose is for irradiation of small samples. It is usually delivered with a 100 kV tube but higher energies are available.*

*This cabinet is made of steel structure covered with leaded panels and is equipped with a heavy duty door providing a very strong behaviour.*

*This enclosure complies with the most severe international regulations on radiation hazards, including NFC 74100 and DIN 54113. The X-ray leakage is reduced to 0,5  $\mu$ Sv/h @ 10 cm from the surface for the proposed X-ray source (public persons).*



### Specifications

Shielded cabinet		
Approximate external size:		
§ Length	mm	600
§ Depth	mm	600
§ Height	mm	750
Manual front loading door aperture	mm	500 x 500
Unloaded weight	kg	1500 (approx.)

Electrical		
Power supply	V	110/220 - 240
Frequency	Hz	50/60

X-ray generator XSD 160		
160 kV very powerful constant potential X-ray generator. DC voltage continuously adjustable from 10 to 100 kV. Standard HV connector.		

Directional X-ray tubehead TSD 100/0	
Metal ceramic X-ray tube	
Spot size (IEC336)	0,6 x 0,6
Nominal (at max 100 kV) mA	6
Beam angle	40°

Directional X-ray tubehead TSD 100/1	
Metal ceramic X-ray tube	
Spot size (IEC336)	1,5 x 1,5
Nominal (at max 100 kV) mA	10
Beam angle	40°

LS1 control unit
Microprocessor based
Internal memory
Large colour screen
Intelligent and users-friendly software

Cables and pipes		
Power and supply cable	m	10
Control, power and security interconnection cables	m	20
100 kV HV cable + earthing cable	m	5
Water pipes	m	5

Misc.
Support for the X-ray tube
Security switch on the door
Labyrinth for cables
Flashing red light during exposure

## Producer

<b>Balteau NDT sa</b> Voie de Liège, 12 B-4681 Hermalle Sous Argenteau BELGIUM  Tel.: +32 4 374 75 75 Fax: +32 4 374 75 85 E-mail: <a href="mailto:balteau@balteau-ndt.com">balteau@balteau-ndt.com</a> Website: <a href="http://www.balteau.com">www.balteau.com</a>
---

## Distributor

